# **Technical Data Sheet**

**CODE 11139** 

# MF 100/4" T HCS LL

Wall axial fans





# Certifications

(4)

IMQ

CE

CE



**IMQ Performance** 

..

EAC.



G-Mark



UKCA


## TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50
Insulation class	II°
IP	X4
Max absorbed current (A)	0,09
Max absorbed power (W)	15
Max ambient temperature for continuous operation (°C)	50
Nominal diameter (mm)	100

Voltage (V)	220-240
Weight (Kg)	0,52
Max airflow (l/s)	24
Max airflow (m³/h)	85
Max pressure (mmH2O)	3
Max pressure (Pa)	29
RPM	2400
Sound pressure Lp [dB (A)] at 3 m	31

## **DIMENSIONS**





Size A (mm)	159
Size B (mm)	17
Size C (mm)	77
Size D (mm)	98

### PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

## **Technical Data Sheet**

#### **CODE 11139**

# MF 100/4" T HCS LL

Wall axial fans



#### **DESCRIPTION**

- Material: UV resistant plastic (prevents ageing caused by exposure to
- Nominal diameter 100 mm.
- Motor protected against thermal overload, with shaft turning in ball bearings, coupled to screw type thermoplastic impeller with wing profile blades.
- Maximum air flow: 85 m3/h.
- ullet Electronic pcb with humidistat function piloted by RH sensor (4 preset thresholds: 60%, 70%, 80%, 90%, selectable during installation),


designed to switch on the fan automatically. The pcb incorporates an electronic timer that shuts off the motor automatically when relative humidity returns below the threshold value. The timer setting is selectable during installation in the range 3'-20' (default setting 3').

Non-return damper fitted to outlet port.

- IMQ SAFETY and IMQ PERFORMANCE certifications.
- · Vortice speed controller.

### **CURVES**

### **ACCESSORIES**



SF 90-100

Code 22162

### PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com UNITED KINGDOM & REP. OF **IRELAND** Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com