

Technical Data Sheet

CODE 15045

TORRETTA TRT 20 ED 4P

Centrifugal roof fans with horizontal discharge for hot fumes extraction




Certifications



TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50	Weight (Kg)	33
Insulation class	I°	Airflow at 1st speed (l/s)	500
Max absorbed current at Max speed (A)	0,53	Airflow at 1st speed (m³/h)	1800
Max absorbed current at Min speed (A)	0,32	Max airflow at Max speed (l/s)	611
Max absorbed power at Max speed (W)	270	Max airflow at Max speed (m³/h)	2200
Max ambient temperature for continuous operation (°C)	90	Max pressure at Max speed (mmH2O)	34
Motor ATEX marking	55	Max pressure at Max speed (Pa)	334
Nominal diameter (mm)	250	Max RPM	1400
Number of phases (Ph)	3	Min RPM	1050
Number of poles	4	Pressure at 1st speed (mmH2O)	24
Power absorbed at 1st speed (W)	208	Pressure at 1st speed (Pa)	235
Voltage (V)	380-415	Sound pressure Lp [dB (A)] at 3 m	68

DIMENSIONS



Size A (mm)	780
Size B (mm)	550
Size C (mm)	500
Size D (mm)	397
Size E (mm)	226
Size F (mm)	38
Size G (mm)	25
Size H (mm)	661
Size L (mm)	231
Size M (mm)	236,5
Size N (mm)	359

PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:

prevendita@vortice-italy.com

After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF

IRELAND

Sales Dept:

sales@vortice.ltd.uk

Technical Dept:

technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:

export@vortice-italy.com

After Sales:

after-sales@vortice-italy.com

Technical Data Sheet

CODE 15045

TORRETTA TRT 20 ED 4P


Centrifugal roof fans with horizontal discharge for hot fumes extraction



DESCRIPTION

- Centrifugal roof fan suitable for extracting hot fumes at up to 400 °C for 120 minutes.
- Base manufactured from phosphated pressed steel, epoxy powder coated with hammered effect finish, guaranteeing long-term resistance to atmospheric agents.
- Aerodynamically contoured inlet port for optimum performance, fashioned as a single unit with the base and gauged to optimize air flow.
- Motor mounting plate made of steel with galvanization surface treatment.
- Pressed steel motor cover: pickled and phosphated surface, polyester powder coated and oven baked finish, colour grey, with hammered texture.
- Accident prevention and anti-bird grilles (to UNI ISO 13857 standard), consisting of electrically welded steel rings with epoxy powder coated finish, colour black.
- Centrifugal impeller with self-cleaning backward curved blades, dynamically balanced (UNI ISO 1940, Point 1 – Class 6.3), made of electrolytically galvanized pressed steel.
- Dahlander 2 speed three-phase AC motor with shaft turning in ball bearings, size to UNEL MEC standard, flange B5, self-ventilating. Motor insulation class H, with metal cooling fan and cable gland.
- Minimum air flow 1800 m³/h
Maximum air flow: 2200 m³/h.
- Equipped with a motor start capacitor that must be installed remotely from the fan so that it cannot be damaged through direct exposure to heat.
- Galvanized steel eye lugs for transport and lifting/handling operations.
- Cable guaranteeing continuity of earth connection.
- Steel safety wire for anchoring the appliance once installed.


CURVES




ACCESSORIES



IRT 15
Code 12923



**TR-CU
20/30/50
(CONTROTELAIO
DI BASE U)**
Code 22512



**TR-G 20/30/50
(GRIGLIA DI
PROTEZIONE)**
Code 22710



PER INFORMAZIONI / FOR INFORMATION

ITALY

Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND

Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES

Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

VELOCITA'

TRIF.)

Code 22910

Code 12010

Code 2112

Code 2113