Technical Data Sheet

CODE 19220

METAL DRY AUTOMATIC

Automatic and manual hand dryers





Certifications

(H)

IMQ

CE CE

C

C Tick Mark


FHI EAC

TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50-60
Insulation class	II°
IP	X4
Max absorbed current (A)	8,5
Max absorbed power (W)	1950
Motor power (W)	140

Shock resistance (IK)	10
Voltage (V)	220-240
Weight (Kg)	7,1
Max airflow (l/s)	53
Max airflow (m³/h)	190
Power in stand-by mode (W)	0,2796
Sound pressure level at 1m Lp [dB (A)]	69,8

DIMENSIONS



Size A (mm)	280
Size B (mm)	355
Size C (mm)	202
Size D (mm)	139

PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 19220

METAL DRY AUTOMATIC

Automatic and manual hand dryers



DESCRIPTION

- Front cover made of pressure diecast aluminium with scratch $resistant\ white\ powder-coated\ finish,\ closure\ with\ vandal-proof\ screws.$
- Plastic wall mounting flange (talc-filled PP).
- Nozzle rotatable through 360°, grille with scratch-resistant powder-coated finish, transparent protection.
- Scroll and motor mounting cowl moulded from ABS
- AC motor with thermal overload cutout and shaft turning in ball bearings, coupled to forward-bladed centrifugal impeller.
- \bullet Heating element protected by 2 devices: thermal fuse and resettable

thermal overload limiter.

- Air flow 190 m3/h.
- \bullet Dryer operated automatically by an infrared device with activation distance of up to 35 cm, selected by means of an internal trimmer adjustable at the moment of installation. Appliance shuts down automatically in the event of the air inlet grille or the warm air outlet nozzle being obstructed intentionally or accidentally.
- IMQ safety certification.

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF **IRELAND** Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com