Technical Data Sheet

CODE 19224

PREMIUM DRY A

Automatic and maual hand dryers




<u>S</u> V	
Certificatio	ons
Ð	IMQ
CE	CE
EHC	EAC

TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50-60	Weight (Kg)	2,3
Insulation class	ll°	Air speed (km/h)	36
IP	Х4	Drying time (s)	30
Max absorbed current (A)	5,5	Max airflow (l/s)	35
Max absorbed power (W)	1350	Max airflow (m³/h)	130
Motor power (W)	45	Max flow speed (m/s)	10
Shock resistance (IK)	09	Power in stand-by mode (W)	0,4550
Voltage (V)	220-240	Sound pressure level at 1m Lp [dB (A)]	55,2

DIMENSIONS



Size A (mm)	253
Size B (mm)	319
Size C (mm)	137
Size D (mm)	220

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

Technical Data Sheet

CODE 19224

PREMIUM DRY A

Automatic and maual hand dryers

DESCRIPTION

- Front cover made of UV-resistant plastic rated V0, colour white. $\boldsymbol{\cdot}$ Wall-mounting flange incorporating warm air outlet grille of moulded

plastic (PP). • EC motor with thermal overload cutout and shaft turning in ball bearings, coupled to forward-bladed centrifugal impeller.

- Heating element protected by 2 devices: thermal fuse and resettable
- thermal overload limiter.
- Air flow 120 m3/h.

• Dust filter.

 $\boldsymbol{\cdot}$ Dryer operated automatically by an infrared device with activation distance of up to 35 cm, selected by means of an internal trimmer adjustable at the moment of installation. Appliance shuts down automatically in the event of the air inlet grille or the warm air outlet nozzle being obstructed intentionally or accidentally. • IMQ safety certification.

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales: postvendita@vortice-italy.com UNITED KINGDOM & REP. OF IRELAND Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com

