Technical Data Sheet

CODE 60643

GORDON W 30/12" ET

Oscillating table, wall-mounting and pedestal fans





Certifications

(H)

IMQ

CE

CE

FAC EAC


TECHNICAL AND PERFORMANCE DATA

Frequency (Hz)	50
Insulation class	II°
IP	20
Max absorbed current (A)	0,18
Max absorbed power (W)	35
Voltage (V)	220-240
Weight (Kg)	2,70

Max airflow (m³/h)	2400
Max airflow (m³/min)	40,00
Max flow speed (m/s)	1,70
Power in stand-by mode (W)	0.4284
RPM	1300
Service value (m³/min)/W	1,143
Sound power Lw [dB(A)]	50.8

DIMENSIONS





Size A (mm)	365
Size B (mm)	550
Size C (mm)	335

PER INFORMAZIONI / FOR INFORMATION

ITALY
Pre Sales:
prevendita@vortice-italy.com
After Sales:
postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF IRELAND
Sales Dept:
sales@vortice.ltd.uk
Technical Dept:
technical@vortice.ltd.uk

OTHER COUNTRIES
Sales Dept:
export@vortice-italy.com
After Sales:
after-sales@vortice-italy.com

Technical Data Sheet

CODE 60643

GORDON W 30/12" ET

Oscillating table, wall-mounting and pedestal fans



DESCRIPTION

- Material: plastic resin able to withstand aging induced by exposure to sunlight (UV-resistant), and formulated with an antistatic compound to prevent accumulation of dust.
- Nominal diameter 300 mm
- 3 speed asynchronous motor with shaft turning in self-aligning and self-lubricating bushings; thermal overload protection.
- Motor housing equipped with hinge and clamp knob for adjustment
- Oscillating mechanism (angle 90°) incorporated into housing, operated by auxiliary asynchronous motor.
- Manual on/off switch and speed selector control; operating status of the fan displayed by luminous indicators located on the base.
- Equipped as standard with IR remote control for switching the fan on and off, selecting the speed, programming the delayed shutoff function (½ h to 7.5 h), and activating the "breeze" option.
- Designed for wall-mounted installation, supplied without power cord.
- Maximum air flow 2,400 m3/h
- IMQ SAFETY and IMQ PERFORMANCE certifications

PER INFORMAZIONI / FOR INFORMATION

ITALY Pre Sales: prevendita@vortice-italy.com After Sales:

postvendita@vortice-italy.com

UNITED KINGDOM & REP. OF **IRELAND** Sales Dept: sales@vortice.ltd.uk Technical Dept: technical@vortice.ltd.uk

OTHER COUNTRIES Sales Dept: export@vortice-italy.com After Sales: after-sales@vortice-italy.com