

ENERGY DATA

CODE 11401

M 150/6"

Wall/window axial fans



| ATTRIBUTO | VALORE ATTRIBUTO |
|---|-----------------------|
| Supplier's name or trade mark | Vortice |
| Specific Energy Consumption (SEC) class in temperate climate zone | NA |
| Specific Energy Consumption (SEC) class in temperate climate zone [kWh/m ² y] | -9,7 |
| Specific Energy Consumption class SEC in cold climate zone [kWh/m ² y] | -23,0 |
| Specific Energy Consumption class SEC in warm climate zone [kWh/m ² y] | -2,0 |
| Declared type | UVR-U: unidirezionale |
| Type of drive | NA |
| Type of heat recovery system HRS | assente |
| Thermal efficiency of heat recovery at reference airflow [%] | NA |
| Max airflow [m ³ /h] | 324 |
| Fan drive electric power input, including any motor control equipment, at maximum flow rate [W] | 27,8 |
| Sound power LWA [dB(A)] | 67 |
| Reference airflow [m ³ /s] | 0,0630 |
| Reference ? pressure [Pa] | 28 |
| SPI [W/(m ³ /h)] | 0,12434 |
| Control factor CTRL | 1 |
| Control type | manuale |
| Max internal leakage rate [%] | NA |
| Max external leakage rate [%] | NA |
| Mixing rate | NA |
| Position and description of visual filter warning | NA |
| Airflow sensitivity to pressure variations at + 20 Pa and – 20 Pa | NA |
| Indoor/outdoor air tightness [m ³ /h] | NA |
| Annual electricity consumption (AEC) [kWh electricity/y] | 171 |
| AHS temperate annual energy saved [kWh primary energy/y] | 1397 |
| AHS cold annual energy saved [kWh primary energy/y] | 2732 |
| AHS warm annual energy saved [kWh primary energy/y] | 632 |